

# Aluminum Economizer Dock Plate 48 In. x 48 In. 1/2 In. Plate Thickness 3800 Lb. Capacity Silver

**MODEL EH-4848**

Loading Dock Equipment / Aluminum Economizer Dockplates

## PRODUCT OVERVIEW

The aluminum economizer dock plate is an economical way to speed up truck loading and unloading. The unit spans the opening between dock and trailer to allow pallet or hand trucks along with traffic to safely move in and out of the trailer. The dock plate is constructed of high strength, non-skid aluminum alloy tread plate. The lightweight design with bolt on zinc plated legs and handles on each side makes portability easy. Locking legs for OSHA compliance. Not for use with fork trucks.

## KEY FEATURES

- Sturdy design is ideal for foot traffic, hand trucks and pallet trucks (not for use with fork trucks)
- High-strength 6061 aluminum tread plate material is durable yet lightweight
- Zinc-plated locking legs and lifting handles are OSHA compliant
- Beveled entrance and exit edges allow for smoother transition

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**118 lbs**

ASSEMBLED SIZE  
**54" W x 48" L x 9.5" H**

SHIP WEIGHT  
**118 lbs**

PACKAGE 1 SIZE  
**48" W x 48" D x 9" H**

COLOR / FINISH  
**Silver**

FREIGHT TYPE  
**LTL Loose**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                                |            |
|------------------------------------------------|------------|
| Uniform Capacity (lb.)                         | 3800       |
| Bend or Crown (degrees)                        | 11         |
| Distance Between Bend or Crown From Dockplat   | 9          |
| Usable Width (in.)                             | 48         |
| Usable Length (in.)                            | 48         |
| Plate Thickness (in.)                          | 1/2        |
| Height Difference Between Truck and Door (in.) | 7          |
| Leg Height (in.)                               | 9          |
| OSHA                                           | 1910.30(a) |
| ANSI                                           | MH 30.2    |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=32>