

# Steel Floor Lock 6-9/16 to 7-5/8 In. Height Silver

**MODEL FL-LKH-6**

Facilities Maintenance / Polyurethane Floor Locks

## PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to create a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

## KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**5 lbs**

**ASSEMBLED SIZE**  
**4.5" W x 7.625" L x 6.5625" H**

**SHIP WEIGHT**  
**5 lbs**

**PACKAGE 1 SIZE**  
**6" W x 8" D x 6" H**

**COLOR / FINISH**  
**Silver**

**FREIGHT TYPE**  
**Parcel**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                          |                                  |
|------------------------------------------|----------------------------------|
| Lowered Height (in.)                     | 6-9/16                           |
| Raised Height (in.)                      | 7-5/8                            |
| Foot Pad Diameter (in.)                  | 3-5/16                           |
| Foot Pad Material                        | Thermoplastic polyurethane (TPU) |
| Grip Pedal Material                      | Thermoplastic polyurethane (TPU) |
| Mounting Plate (in.)                     | 3-15/16 x 4-1/2                  |
| Slotted Holes on Center (in.)            | 3-1/16, 3-11/16                  |
| Mounting Plate Thickness (in.)           | 3/16                             |
| Slotted Mounting Hole Width/Height (in.) | 3/8 x 13/16                      |
| Inside Bolt Hole Spacing (in.)           | 2-9/16 X 3-3/16                  |
| Outside Bolt Hole Spacing (in.)          | 3-3/16 X 3-11/16                 |
| Suggested Caster Size (in.)              | 6                                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1067>