Steel Quick Lift DC Powered Lift 57 In. Raised Height 400 Lb. Capacity

MODEL PEL-400S-57-D3

Ergonomic Solutions / Powered Quick Lifts

PRODUCT OVERVIEW

The DC powered quick lift is a quiet, lightweight unit used for transport and positioning loads quickly with just the push of the button. The unit is battery operated with a high density polyethylene platform. It features a low profile design for maneuvering in narrow aisles and confined spaces. This quick lift comes with rigid front wheels and swivel rear wheels with locks. The DC system runs with an AC on-board charger. The steel unit has a powder coat blue finish with custom end attachments available.

KEY FEATURES

- DC powered battery is fast and quite
- White HDPE platform offers durability and aesthetics
- Chain driven platform operation provides precise positioning
- Touch-pad control allows for easy operation

CORE PRODUCT DATA

ASSEMBLED WEIGHT **372 lbs**	ASSEMBLED SIZE **24.125" W x 44.875" L x 67.25" H**	SHIP WEIGHT **427 lbs**
PACKAGE 1 SIZE **40" W x 48" D x 74" H**	COLOR / FINISH **Blue**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	400
Lowered Height (in.)	6-1/2
Raised Height (in.)	57
Caster Diameter (in.)	4
Caster Type	(2) Rigid (2) Swivel with Brake
Caster Material	Poly-on-Poly
DC Voltage	24
AC Charger Voltage	115
Horizontal Load Center (in.)	9
Includes	Fully Welded Frame
Handle Length (in.)	6
Handle Material	Steel
Platform Width (in.)	24
Platform Length (in.)	20
Platform Thickness (in.)	1/2
Battery Depth	8
Battery Width	12
Battery Height	7
Battery Weight	48
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?FID=260