Steel Pallet Master/Server Stacker 12 Volt DC Powered 60 In. Raised Height 4,000 Lb. Capacity Blue

MODEL PMPS-60-DC

Ergonomic Solutions / Pallet Master/Servers



PRODUCT OVERVIEW

The pallet master/server enables one person to easily move fully loaded pallets without the use of a fork truck. The unique straddle design works well with pallets and skids with and without an understructure. The unit is ideal for loading and unloading semi-trailers. Hand pendant control on an eight (8) foot coil cord standard. Floor lock standard. All welded steel construction.

KEY FEATURES

- Easily move fully loaded pallets enabled by one person
- Straddle design works pallets and skids with or without an understructure
- Ideal for loading and unloading semi-trailers without strenuous work
- Hand pendant control on an eight (8) foot coil cord standard

CORE PRODUCT DATA

ASSEMBLED WEIGHT **1029 lbs**	ASSEMBLED SIZE **58" W x 66" L x 87" H**	SHIP WEIGHT **1060 lbs**
PACKAGE 1 SIZE **64" W x 64" D x 94" H**	COLOR / FINISH **Blue**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS






PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Operation	(1) 12V DC
Fork Width/Length (in.)	4 x 36
Service Range (in.)	3 to 60
Adjustable Fork Spacing (in.)	8 to 37
Leg Spacing (in.)	49-1/2
Handle Height (in.)	36
Coil Cord Length (in.)	96
Rear Swivel Caster Quantity/Diameter/Width (in.)	(2) 8 x 3
Rear Caster Material	Phenolic
Front Wheel Quantity/Diameter/Width (in.)	(2) 8 x 2
Front Wheel Material	Glass Filled Nylon
Overall Width (in.)	58
Overall Length (in.)	66
Overall Raised Height (in.)	101
Overall Lowered Height (in.)	87
Maximum Fork Height Before Carriage Exceeds H	42
Steel Construction	ASTM A-36 Minimum
Battery Depth	11
Battery Width	7
Battery Height	9
Battery Weight	42
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=243