Steel Counter Balanced Powered Lift 2 In. to 62 In. Raised Height 2,000 Lb. Capacity Black / Yellow

MODEL S-2CB-62

Ergonomic Solutions / Counter-Balanced Powered Drive Lifts



PRODUCT OVERVIEW

Counter balance design is ideal for die loading, machine feeding, and for loading and unloading trucks. High torque drive and lift motor handles heavy-duty jobs. Ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. Includes an electromagnetic disc brake with automatic dead-man feature that activates when the user releases, the handle. Powered lift also includes batteries, an integral battery charger, and battery level gauge. Adjustable forks suitable for different pallets. A high level of serviceability simplifies maintenance and prolongs equipment life. Easy access battery compartment simplifies battery mai...

KEY FEATURES

- Simple controls for quick movement
- Walk behind style for ergonomic posture
- Ability to raise to high levels of workspace
- Poly-on-steel steer and load wheels

CORE PRODUCT DATA

ASSEMBLED WEIGHT **2628 lbs**	ASSEMBLED SIZE **35.5" W x 110" L x 78" H**	SHIP WEIGHT **2496 lbs**
PACKAGE 1 SIZE **46" W x 101" D x 84" H**	COLOR / FINISH **Black & Yellow**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS







PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,000
Service Range (in.)	2 to 62
Fork Width/Length (in.)	4 x 36-1/4
Adjustable Fork Spacing (in.)	8-3/8 to 23-1/4
Drive Motor	24V / 1 KW
Lift Motor	24V / 2 KW
Battery	(2) 12V / 135 Ah
Battery Charger	24V / 12 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Travel Speed - Unloaded (MPH)	3.43
Travel Speed - Loaded (MPH)	2.8
Platform Ground Clearance (in.)	1-1/2
Load Center (in.)	19
Mast Style	Fixed
Lift Speed w/o Load	5.9" / sec
Lift Speed w/ Load	2.95" / sec
Lower Speed w/o Load	4" / sec
Lower Speed w/ Load	3.15" / sec
Battery Depth	14
Battery Width	14
Battery Height	10
Battery Weight	112
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=254