

Polyurethane Wheel Chock 15 In. x 25 In. x 16 In. Tire Overall Depth 165 In. 400 Ton Capacity Yellow

MODEL URWC-HD-32

Loading Dock Equipment / Urethane Wheel Chocks



PRODUCT OVERVIEW

When it comes to maintaining strength and stability look no further than the polyurethane wheel chock. With a wide foundational base the chock can keep loads of many sizes safe and secure from movement or jostling. A handle is included in the back for easy carrying and transference from place to place, while there are pre drilled mounting holes if the location is more permanent. The bright color encourages clear visibility and awareness.

KEY FEATURES

- Polyurethane construction for continued durability
- Built in bar style handle for simple grasping and carrying
- Large capacity to handle a variety of load sizes
- Resistant to a variety of chemicals

CORE PRODUCT DATA

ASSEMBLED WEIGHT
32 lbs**ASSEMBLED SIZE**
15" W x 25" L x 16" H**SHIP WEIGHT**
33 lbs**PACKAGE 1 SIZE**
16" W x 26" D x 17" H**COLOR / FINISH**
Yellow**FREIGHT TYPE**
Parcel**AVAILABILITY** Quote Required - Please Contact Sales**QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (tons) GVWR	400
Fits Tire Size (in.)	Up to 165

PRODUCT & SHIPPING REFERENCE

Shipping Point:	Henderson CO 80640	Warranty:	30 Days
-----------------	--------------------	-----------	---------

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=81>